



CWELED-TH-DS-RAOW

IP66/67 Weatherproof Exit, Surface Mount, LP, Clevertest Plus, Theatre Version, Running Man Arrow One Way, Double Sided



PRODUCT INFORMATION

Part Number	CWELED-TH-DS-RAOW
MIC	AUA02360470001
Description	IP66/67 Weatherproof Exit, Surface Mount, LP, Clevertest Plus, Theatre Version, Running Man Arrow One Way, Double Sided
Construction	Polycarbonate Clear Cover, Glass Reinforced Nylon PA66 Base
Mounting	Wall, Ceiling Single-sided & Ceiling Double-sided
Dimensions L x W x H	410mm x 100mm x 272mm
Weight	3.4kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not Activated by Default)
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Theatre Mask, Running Man Arrow One Way
Lamp(s)	6 x LED 100,000 hours
Operating Voltage	240V AC; 50Hz
Supply Current	0.044A
Power Factor	0.368
Power Consumption	1.8W/3.2W (Standby/Max)
Inrush Current (Peak/Duration)	12.517A / 82µs
Earth Leakage	0.333mA
IP Rating	IP66/IP67
IK Rating	IK10
Operating Temperature	0°C to 40°C
AS2293 Classification	N/A
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	
Appliance Class	 Class II Double Insulated  Noiseless (Clean) Earth (Ground) Terminal (Not a Protective Earth and used for EMC purposes only)

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550105	Battery
8002710	LED Panel
8002301	Emergency Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order