

# MERCURY CORE

Mercury Core Emergency Exit, 24m

- Single and double sided decals
- Fully compliant (AS/NZS 2293)
- IP65 Weatherproof Case available but not included
- Wall, ceiling, chain and rod mounting (with Rod Mount Kit)
- Long life electronics
- 6 Years Design Life at max. ambient
- High Quality Lithium battery (LiFePO4) and smart charger
- Standalone (SPU)



## ORDERING INFORMATION

Order code	11802
Description	Mercury Core Emergency Exit 24m - Black
Item Code	EV-MERCURY-CORE-24M-B

## MECHANICAL

Fitting Colour	Black
----------------	-------

## ELECTRICAL

Input Frequency	50 Hz
Input voltage	230Vac
In Australia the Input voltage is defined as 230Vac -6%/+10%. This effectively means that the voltage range of these products are 216Vac - 253Vac or 240V +6%	

## DRIVER

Driver Included	Yes
Integrated Driver	Yes

## EMERGENCY (EM SUFFIX)

Emergency Mode	Maintained
Emergency Duration	90 mins
Viewing Distance	24 m

## COMPLIANCE

Product Design Life	6 years
The product design life relates to the total product life which includes LEDs, drivers and the enclosure. This is different to the LED lifetime which only refers to the economical lifetime of the LEDs at which time the lumen output has dropped below the L Value. The product design life is calculated at the maximum ambient or working temperature of the product and takes into account the Daily Use.	
Standards	AS/NZS 60598.1
	AS 60598.2.22
	AS/NZS 61347.1
	AS/NZS 61347.2.13
	AS CISPR 15
	AS/NZS 2293.3

## WARRANTY

Commercial Use Warranty	5 RTB (Total 5 Years)
-------------------------	-----------------------

## DIMENSIONS

**Product Height** 211 mm

**Product Length** 326 mm

**Product Width** 80 mm

## LINE DRAWINGS

EV/MERCURY/CORE/24M

