

PORTLAND II

GPO325

DECORATIVE LED BULKHEAD LIGHT



FEATURES

- ABS body and opal polycarbonate diffuser
- Twist and lock diffuser for fast installation
- High efficiency up to 140lm/W
- Switchable wattage and CCT
- Choice of alternative decorative trims
- Constant current LED driver fitted
- Power factor: 0.95
- Colour matching 6 MacAdam steps
- LED lifespan: 50000 hours @ L70 B10, Ta 25°C
- Ta: -20°C to +50°C



EMERGENCY

- Intelligent automatic recharging function
- Compliant to AS/NZS 2293
- Constant current mode
- 3 hour emergency operation
- Output wattage 1.5W
- Over-discharge protection
- LED charge status display
- Test switch with self-test function
- Ta: 0°C to +40°C

TECHNICAL DATA

Rated supply voltage: 230V~	Recharge hours: 24h
Frequency: 50/60Hz	LED indicator power: 0.06W
Input power: 2W	Battery type: LiFePO4 18650 3.2V 1.8Ah

CLASSIFICATION: C0: D50, C90:D32 (120) / C0: D40, C90:D32 (150)

TECHNICAL SPECIFICATIONS

MODEL NO.	INPUT VOLTAGE (V)	POWER (W)	OUTPUT CURRENT (mA)	LUMEN (lm)	COLOUR TEMPERATURE (K)	CRI	BEAM ANGLE (°)	FITTING COLOUR	CARTON QUANTITY
GPO325 QC WH	230	16	110	2240	3000/4000/5000/6000	>80	120	White	10

DECORATIVE TRIMS

MATTE BLACK RING

EYELID BLACK RING

EYELID WHITE RING



GPO325 QC BK



GPO325 QC EK




GPO325 QC EW

OPTIONS


- PLUG AND PLAY EMERGENCY KIT
-GPO325/EM KIT



- PLUG AND PLAY MOTION SENSOR
-GPO325/MOTION SENSOR



DIMENSIONS



Unit: mm