



R729	Mini
Dimensions D70 x H91mm	Cut Out Ø57mm
Watts Selectable 5.3W-8.5W	Lumens <700lm
Beam 45°	



R730	Standard
Dimensions D93 x H105mm	Cut Out Ø 72-82mm
Watts 9.5W	Lumens <950lm
Beam 50°	



R731	Standard Wide Beam
Dimensions D93 x H105mm	Cut Out Ø 72-82mm
Watts 9.5W	Lumens <930lm
Beam 90°	

Specifications

Input	240V AC
Colour Temp	2700K, 3000K, 4000K, 2700K-6500K
CRI	90
Lifespan	R729 R730: 105,000hrs (L80 B10). R731: 102,000 hours (L80 B10). Casambi: 55,000hrs (L80 B10).
Binning	SDCM 3
Material	Aluminium, PC, PA and PMMA
IP Rating	IP65 (room side)
Clearance	25mm recommended for optimum lifespan. 0mm required. Rear of fitting may abut structural members and building elements.
Classification	IC-F / IC-4
Driver	Included, Under Insulation (Tunable White Casambi driver must be installed above insulation).
Dimming/Control	Phase-cut Dimmable, Casambi
TLAs	"Flicker-free", PstLM ≤ 1.0 ; SVM ≤ 0.4
Application	Interior, recessed
Warranty	5 Year Warranty

Lumens

	White	Black
R729	<490lm @ 5.3W <610lm @ 6.5W <700lm @ 7.9W <730lm @ 8.5W	<460lm @ 5.3W <550lm @ 6.5W <650lm @ 7.9W <680lm @ 8.5W
R730	<950lm	<910lm
R730 Casambi	<880lm	<820lm
R731	<930lm	<630lm



White



Black

Available In

Description	Code
R729 - Mini 45°	
White 2700K	R729-W27KA-D-GL
White 3000K	R729-W3KA-D-GL
Black 2700K	R729-B27KA-D-GL
Black 3000K	R729-B3KA-D-GL
R730 - Standard 50°	
White 2700K	R730-W27KV2
White 3000K	R730-W3KV2
White 4000K	R730-W4KV2
Black 2700K	R730-B27KV2
Black 3000K	R730-B3KV2
Black 4000K	R730-B4KV2
R731 - Standard Wide Beam 90°	
White 2700K	R731-W27KV2
White 3000K	R731-W3KV2
White 4000K	R731-W4KV2
Black 2700K	R731-B27KV2
Black 3000K	R731-B3KV2
Black 4000K	R731-B4KV2

CASAMBI

Description	Code
R730 - Casambi Small 50°	
White, 2700K-6500K Tunable White	R730 WCCTCAS
Black, 2700K-6500K Tunable White	R730 BCCTCAS



R729, and R730 Casambi Tunable White are pre-wired with GL240 adaptor



<50° optics low glare lens



90° Wide beam with opal diffuser