

LXT | **18V**

POWERFUL ILLUMINATION

DML819
MAGNETIC LIGHT

UP TO **1,200** LM
MAXIMUM
BRIGHTNESS

UP TO **22** HOURS
RUNTIME
ON LOW SETTING USING BL1860B

UP TO **2.4M**
ILLUMINATION
COVERAGE HORIZONTAL
FACING



DML819



DML816



DML801



DML817



DML807



DML812



MODE 1: SPOT
MODE 2: FLOOD
MODE 3: SPOT-FLOOD
MODE 4: STROBE

MODE 1: 600LM
MODE 2: 1,000LM
MODE 3: 1,250LM

LUMINOUS FLUX

1200LM | 800LM | 500LM

500LM | 250LM | 100LM

240LM | 120LM

300LM | 150LM
LAMP SHADE: 160LM | 130LM

SIDE LIGHT: 710LM | 340LM
TOP LIGHT: 130LM

COLOUR TEMPERATURE

DAYLIGHT WHITE (5,000K)

DAYLIGHT WHITE (5,000K)

DAYLIGHT WHITE (5,000K)

DAYLIGHT WHITE (5,000K)
WARM LAMP SHADE (2,500K)

DAYLIGHT WHITE (5,000K)

WHITE

LIGHTING COVERAGE

FORWARD: UP TO 2.3M
HORIZONTAL: UP TO 2.4M

-

-

-

-

MODE 1: Up to 640M

LIGHT ANGLE ADJUSTMENT

VERTICAL: 180°
HORIZONTAL: 300°
HORIZONTAL: 90° RIGHT | 210° LEFT

VERTICAL: 180°
HORIZONTAL: 300°
HORIZONTAL: 90° RIGHT | 210° LEFT

VERTICAL: 180°
HORIZONTAL: 300°
HORIZONTAL: 90° RIGHT | 210° LEFT

-

-

VERTICAL: 90°

APPROX. CONTINUOUS RUNTIME (WITH BL1860B)

HIGH: 9HRS
MED: 14HRS
LOW: 22HRS

HIGH: 17HRS
MED: 34HRS
LOW: 75HRS

HIGH: 20HRS
LOW: 48HRS

HIGH: 28HRS
LOW: 49HRS

(SIDE) - HIGH: 14HRS | LOW: 28HRS
(TOP): 43HRS

MODE 1: 10HRS | MODE 2: 7.5HRS
MODE 3: 6HRS | MODE 4: 8.5HRS

DIMENSIONS (L x W x H)

172MM x 91MM x 161MM
(FOLDED CLOSED)

109MM x 79MM x 221MM
(FOLDED CLOSED)

95MM x 79MM x 200MM
(FOLDED CLOSED)

107MM x 77MM x 50MM

102MM x 79MM x 317MM

115MM x 119MM x 268MM

WEIGHT (SKIN)

0.88KG

0.41KG

0.33KG

0.21KG

0.32KG

0.89KG

WEIGHT (WITH BL1850B)

1.58KG

1.09KG

1.01KG

0.89KG

1.0KG

1.57KG

ML187



DML815



DML808



DML809



DML818



DML814



	ML187	DML815	DML808	DML809	DML818	DML814
LUMINOUS FLUX	48LM	160LM	190LM	10,000LM 4,000LM 2,000LM	1,700LM 800LM 400LM	3,000LM 1,700LM 900LM
COLOUR TEMPERATURE	WHITE	WHITE	WHITE	DAYLIGHT WHITE (5,000K)	DAYLIGHT WHITE (5,000K)	DAYLIGHT WHITE (5,000K)
LIGHTING COVERAGE	-	-	-	10M	UP TO 3.3M	UP TO 5.6M
LIGHT ANGLE ADJUSTMENT	VERTICAL: 110°	VERTICAL: 170°	VERTICAL: 170°	VERTICAL: 270°	VERTICAL: 180°	VERTICAL: 110° HORIZONTAL: 220° LIGHT PIVOT: 90° UP & DOWN
APPROX. CONTINUOUS RUNTIME (WITH BL1860B)	81HRS	54HRS	32HRS	HIGH: 1.7HRS MED: 4.5HRS LOW: 8.5HRS (2x BL1860B)	HIGH: 5HRS MED: 11HRS LOW: 23HRS (UPPER & LOWER BARS ON)	HIGH: 3.6HRS MED: 6.6HRS LOW: 12HRS
DIMENSIONS (L x W x H)	118MM x 79MM x 288MM (FOLDED UPWARDS)	116MM x 79MM x 227MM (FOLDED UPWARDS)	119MM x 79MM x 252MM (FOLDED UPWARDS)	370MM x 249MM x 370MM	972MM x 80MM x 134MM (FOLDED OPEN)	260MM x 216MM x 1,000MM (FOLDED) 573MM x 658MM x 2,240MM (EXTENDED)
WEIGHT (SKIN)	0.42KG	0.26KG	0.43KG	5.7KG	1.1KG WITHOUT TELESCOPIC HOOK	7.4KG
WEIGHT (WITH BL1850B)	1.1KG	0.93KG	1.11KG	6.38KG	1.78KG WITHOUT TELESCOPIC HOOK	8.08KG

SPECIFICATIONS

LUMINOUS FLUX	1200LM 800LM 500LM
COLOUR TEMPERATURE	DAYLIGHT WHITE (5,000K)
LIGHTING COVERAGE	FORWARD: UP TO 2.3M HORIZONTAL: UP TO 2.4M
LIGHT ANGLE ADJUSTMENT	VERTICAL: 180° HORIZONTAL: 300° HORIZONTAL: 90° RIGHT 210° LEFT
CONTINUOUS RUNTIME (WITH BL1860B)	HIGH: 9HRS MED: 14HRS LOW: 22HRS
DIMENSIONS (L x W x H)	172MM x 91MM x 161MM (FOLDED CLOSED)
WEIGHT (SKIN)	0.88KG
WEIGHT (WITH BL1850B)	1.58KG

HIGHLIGHTS



ADJUSTABLE ILLUMINATION

Features a foldable rotating LED head that offers 180° vertical and 300° horizontal rotation. Ensuring flexibility in directing light where you need it most.



HANDS FREE OPERATION

Use the strong magnetic base or the optional vice clamp too attach the light to almost any surface. Perfect for maintenance tasks in any work environment.



COMPACT DESIGN

Folds down to an incredibly compact and lightweight unit. Taking up minimal storage space without sacrificing performance.



TOOL HOOK

Hang the light using the built-in tool hook. Simply fold the hook from the base.

FEATURES

POWERFUL ILLUMINATION: Delivers a maximum brightness of 1,200 lumens, with adjustable settings for high (1,200lm), medium (800lm), and low (500lm) to suit any work environment.

HANDS FREE CONVENIENCE: Equipped with powerful magnetic bars, this light easily attaches to ferrous metal surfaces enabling hands-free operation.

COMPACT & PORTABLE DESIGN: Engineered to be incredibly compact and lightweight, allowing for easy handling and storage without sacrificing performance.

EYE-FRIENDLY TECHNOLOGY: Designed with a diffusing lens to minimise overlapping shadows and glare, reducing eye strain for extended use.

SMART BATTERY MANAGEMENT: The battery capacity warning function alerts you when power is low, gradually dimming the LED's for a smoother transformation to ensure you're never left in the dark.



STANDARD ACCESSORIES

TD00000204

Magnet Cover



OPTIONAL ACCESSORIES

GM00001396

Vise Clamp



1915A5-9

18V LXT 5.0Ah Battery and
Charger Kit

