

CSB18FW

NHP MOD6 CSB Insulated Loadcentre 18 Way DIN Flush Door
White



MOD6

LOADCENTRES AND POLE COVERS



Component type	Small distribution board
Range	CSB
Model	N/A
Product status	Existing

NHP's CSB surface-mounted insulated loadcentres offer a compact, cost effective method of mounting DIN circuit protective devices in domestic or commercial settings. The CSB loadcentres can accommodate a wide range of current ratings, making them suitable for various applications. The CSB surface or flush-mount options range from 8 up to 36 way with either transparent or white door.

ELECTRICAL

Rated current In	100 A
Number of outgoing ways	18
Number of poles, 18mm pitch	18
Max. rated operation voltage Ue AC	415 V
Rated insulation voltage Ui	500 V
Neutral terminal block	Yes
Neutral bar rated current	100 A
Earthing terminal block	Yes

CONSTRUCTION

Spare DIN equipment space (poles)	18
DIN-rail	Yes
Number of rows	1
Material housing	Plastic
Colour	White
IP rating	IP40
Type of cover	Door
Transparent cover/door	No
With lock	No
Mounting method	Recessed

DIMENSIONS

Width in number of modular spacings	18
Height	267 mm
Width	412 mm
Depth	105 mm
Built-in depth	76 mm
Built-in height	232 mm
Built-in width	380 mm

CSB18FW

NHP MOD6 CSB Insulated Loadcentre 18 Way DIN Flush Door
White




MOD6

LOADCENTRES AND POLE COVERS

RELATED PRODUCTS

ACCESSORY



Item No: CSB18FMPL

Required: No

Description: NHP MOD6 CSB Insulated Loadcentre Metal Back Mounting Plate Long suits CSB18 Flush