



**Nexans**  
**Ref.:** APAQ05AA012CXWW  
**Country Ref.:** 8983  
**EAN 13:** 9319215455279

#### CONTACT

Sales and Customer Solutions  
Phone: 0800 639 267  
sales.nz@nexans.com

Cu conductors, PVC insulation (numbered cores), Laid up, Black PVC sheath. 450/750 V.  
Made to AS/NZS 5000.3,

#### STANDARDS

**Product** AS/NZS 5000.3

#### Application

- Industrial and commercial applications
- Used as a connections type of cable between control cabinets where a number of control signals are required; or for use in any areas where control of equipment is required.
- Both unarmoured and armoured controls are used in a similar style of application, the only difference being that in the case of unarmoured cable the customer may require mechanical protection of the cable.

### CHARACTERISTICS

#### Construction characteristics

Conductor material	Copper
Insulation	PVC
Outer sheath	PVC
Core identification	Black numbers

#### Dimensional characteristics

Number of cores	12
Conductor cross-section	1.5 mm <sup>2</sup>
Nominal overall diameter	15.3 mm
Gland Size (A2 or A2F)	25
Approximate weight	0.38 kg/m

#### Electrical characteristics

Max. DC resistance of the conductor at 20°C	13.6 Ohm/km
Rated Voltage U <sub>0</sub> /U	450/750 V
Rated Voltage U <sub>0</sub> /U (U <sub>m</sub> )	-

#### Usage characteristics

Max. conductor temperature in service	75 °C
---------------------------------------	-------

### CURRENT CARRYING CAPACITIES (IN AMPS) - CONTROL CABLES

Control cables

Conductor cross-section [mm <sup>2</sup> ]	 Cu	 Cu	 Cu	 Cu
1.5	21	33	17	28.6
 Unenclosed touching 2 cond.	 Voltage Drop 2 Cond. Single Phase (mV/A.m)		 Unenclosed touching 3 cond.	
 Voltage Drop 3 Cond. Three phase (mV/A.m)				

#### Note

- Content from AS/NZS 3008.1.2:2010 has been reproduced with the permission from Standards New Zealand under Copyright Licence 000926. Please see the Standard for full details.
- The values in this table are for typical New Zealand installation conditions of:  
Ambient Air Temperature 30°C