



Nexans
Ref.: BAAP05A1001AAWT
Country Ref.: 3317.1
EAN 13: 9319215005900

CONTACT

Sales and Customer Solutions
Phone: 0800 639 267
sales.nz@nexans.com

Cu conductor, PVC insulation. 0.6/1 kV. Made to AS/NZS 5000.1.

STANDARDS

Product AS/NZS 5000.1

Application

- Industrial, commercial and domestic applications
- The wiring of switch boards and control panels
- Earth wiring in houses
- Wiring where the conduit wire is run inside a protective enclosure (plastic or metal conduits)

CHARACTERISTICS

Construction characteristics

Colour	White
Insulating material	PVC
Type of conductor	Circular, stranded
Conductor material	Copper
Insulation	V-90
Conductor flexibility	Class 2
Conductor shape	Circular
With Green/Yellow core	No
With smaller neutral conductor	No

Dimensional characteristics

Conductor cross-section	1.5 mm ²
Nominal overall diameter	3.3 mm
Approximate weight	0.02 kg/m
Neutral conductor section (when smaller)	- mm ²
Number of cores	1

Electrical characteristics

Max. DC resistance of the conductor at 20°C	13.6 Ohm/km
Permissible short circuit current conductor 1s	- kA
Rated Voltage U ₀ /U (U _m)	0.6/ 1 (1.2) kV

Mechanical characteristics

Cable flexibility	Rigid
-------------------	-------

Usage characteristics

Max. conductor temperature in service	90 °C
---------------------------------------	-------

CURRENT CARRYING CAPACITIES SINGLE PHASE (IN AMPS) - CONDUIT WIRES

Copper conductor Circular stranded (except 1 mm² which is solid) Insulation PVC Max. Conductor Temperature 75C

Conductor cross-section

[mm²]

1.5



Cu

21



Air enclosed

Note

© Copyright Standards New Zealand 2016.

Content in this table and the typical New Zealand installation conditions are derived from AS/NZS 3008.1.2:2010 and has been reproduced or adapted with permission from Standards New Zealand under Copyright Licence 000926. Please refer to the complete Standard for full details available for purchase from Standards New Zealand at www.standards.co.nz.

The values are for typical New Zealand installation conditions of:

- Ambient Air Temperature: 30°C

CURRENT CARRYING CAPACITIES THREE PHASE (IN AMPS) - CONDUIT WIRES

Copper conductor Circular stranded (except 1 mm² which is solid) Insulation PVC Max. Conductor Temperature 75C

Conductor cross-section [mm ²]	 Cu
1.5	17

 Air enclosed

Note

© Copyright Standards New Zealand 2016.

Content in this table and the typical New Zealand installation conditions are derived from AS/NZS 3008.1.2:2010 and has been reproduced or adapted with permission from Standards New Zealand under Copyright Licence 000926. Please refer to the complete Standard for full details available for purchase from Standards New Zealand at www.standards.co.nz.

The values are for typical New Zealand installation conditions of:

- Ambient Air Temperature: 30°C