



Nexans
Ref.: FEGG21PX003CXRJ
Country Ref.: 8365
EAN 13: 99416079021053

CONTACT

Sales and Customer Solutions
 Phone: 0800 639 267
 sales.nz@nexans.com

Al conductors, XLPE insulation, Laid up, Cu neutral screen, Black PVC sheath. 0.6/1 kV. Made to AS/NZS 4961.

STANDARDS

Product AS/NZS 4961

Application

- Industrial, commercial and domestic applications.
- For use in various situations to supply the main power from the point of supply to buildings, equipment shed, e.g. switch board to main control cabinet, main between floors and buildings, cable cabinet to motor, etc.



Conductor flexibility
Class 2



Rated Voltage U₀/U (Um)
0.6/ 1 (1.2) kV



Cable flexibility
Rigid



Max. conductor temp. in service
90 °C



U.V resistance
Yes

CHARACTERISTICS

Construction characteristics

Pilot wires	None
Type of conductor	Sector-shaped, stranded
Sheath colour	Black
Conductor material	Aluminum
Insulation	XLPE
Screen	Copper wire
Outer sheath	PVC
Conductor flexibility	Class 2
Conductor shape	Circular
Core identification	Red, White Blue
With Green/Yellow core	No
With smaller neutral conductor	No

Dimensional characteristics

Number of cores	3
Conductor cross-section	95 mm ²
Nominal overall diameter	35.9 mm
Nominal overall diameter	-
Approximate weight	2.01 kg/m
Neutral conductor section (when smaller)	- mm ²

Electrical characteristics

Max. DC resistance of the conductor at 20°C (Ohm/km)	0.32
Permissible short circuit current conductor 1s	- kA
Rated Voltage U ₀ /U (U _m)	0.6/ 1 (1.2) kV

Mechanical characteristics

Cable flexibility	Rigid
-------------------	-------

Usage characteristics

Max. conductor temperature in service	90 °C
U.V resistance	Yes

CURRENT CARRYING CAPACITIES(IN AMPS) - AL NEUTRAL SCREEN CABLES 3 CORE THREE PHASE

Aluminium conductor 35 and 50 mm² Circular compacted, 70 and 95 mm² Shaped stranded Insulation XLPE Max. Conductor Temperature 90C

Conductor cross-section [mm ²]	 AI	 AI	 AI	 AI	 AI
95	242	224	178	250	194
 Air Spaced from Surface, Unenclosed	 Air touching, unenclosed	 Air enclosed		 Buried direct	 Buried in single-way duct

Note

Content from AS/NZS 3008.1.2:2010 has been reproduced with the permission from Standards New Zealand under Copyright Licence 000926. Please see the Standard for full details.

The values in this table are for typical New Zealand installation conditions of:

- Ambient Air Temperature 30°C
- Soil Temperature: 15°C
- Soil Thermal Resistivity: 1.2 K.m/W
- Depth of Burial: 0.5 m