



12W Eco Oyster Light
Ø255mm
PLECL12W

FEATURES

- Light weight and easy to install
- Metal housing with PMMA diffuser
- CCT selectable 3000K, 4000K, 5700K
- Flicker free, triac dimmable driver
- Surface mounted

CERTIFICATIONS



PRODUCT INFORMATION





18W Eco Oyster Light
Ø330mm
PLECL18W



24W Eco Oyster Light
Ø380mm
PLECL24W

TECHNICAL SPECIFICATIONS

Product	Eco Oysters		
Ordering Code	PLECL12W	PLECL18W	PLECL24W
Power (W)	12	18	24
Colour Temperature (K)	3000 / 4000 / 5700	3000 / 4000 / 5700	3000 / 4000 / 5700
Lumen Output (lm)	1120-1240	1630-1800	2180-2400
CRI	>80	>80	>80
Beam Angle	120°	120°	120°
Dimming	Triac Dimming	Triac Dimming	Triac Dimming
LED Type	SMD	SMD	SMD
IP Rating	IP44	IP44	IP44
IK Rating	IK05	IK05	IK05
Input Voltage	220-240V AC	220-240V AC	220-240V AC
Electrical Class	Class I	Class I	Class I
Power Factor	0.9	0.9	0.9
Operating Temperature	-10°~45°C	-10°~45°C	-10°~45°C
Lifetime (hr)	50,000	50,000	50,000
Installation	Surface Mount	Surface Mount	Surface Mount
Dimensions (mm)	Ø255 x 74	Ø330 x 74	Ø380 x 74
Fitting Colour	White	White	White